

S A	SKU #	✓ 60 Hz	✓ CSA / UL approved	✓ 1 Phase Control Panel	3 Phase Control Panel	✓ 460/480 volt	575/600 volt	Minimum Component Rating Amperage	Maximum IG Nameplate Amperage	Maximum IG Nameplate Rating (Hp) ^{Note 2}	Maximum IG Nameplate Rating (Kw)	Maximum IG Output (Hp)	Maximum IG Output (Kw)	✓ Panel Meter	✓ Automatic restarting	✓ SEL 547 Interconnection Relay	SEL 700GT Interconnection Relay	✓ Soft Starting	✓ AC Brake control	Touch Safe Power and Terminal blocks	✓ ATDR fuses	✓ Fused Disconnect	✓ Allen-Bradley PLC	PLC programmed and tested prior to shipment	SEL Relay programmed and tested prior to shipment	As built drawings and component literature	Protection and Control Document	Accessory Inputs (vibration/level switches)	✓ Wall Mounted Enclosure	Floor mounted enclosure	Power Consumption of panel under full load (W)	Retail Price		
	1-460/480-20-547	✓	✓	✓		✓		25	20	15	11	8	6	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	117	\$7,769.61		
	1-460/480-40-547	✓	✓	✓		✓		50	40	30	22	15	11	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	117	\$8,152.29		
	1-460/480-72-547	✓	✓	✓		✓		90	72	60	45	31	23	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	117	\$9,084.24		
B	1-460/480-48-700GT	✓	✓	✓		✓		60	48	30	22	15	11	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	302	\$19,081.64		
	1-460/480-80-700GT	✓	✓	✓		✓		100	80	60	45	31	23	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	302	\$20,164.18		
	1-460/480-112-700GT	✓	✓	✓		✓		140	112	75	56	38	29	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	312	\$22,998.39		
	1-460/480-160-700GT	✓	✓	✓		✓		200	160	125	93	64	48	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	308	\$25,266.34		
	1-460/480-200-700GT	✓	✓	✓		✓		250	200	150	112	77	57	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	308	\$26,668.28		
	1-460/480-240-700GT	✓	✓	✓		✓		300	240	220	164	113	84	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	323	\$28,325.09		
	1-460/480-320-700GT	✓	✓	✓		✓		400	320	275	205	141	105	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	352	\$31,090.66		
	1-460/480-480-700GT	✓	✓	✓		✓		600	480	300	224	154	115	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	402	\$43,954.94		
C	1-575/600-48-700GT	✓	✓	✓		✓		60	48	50	37	26	19	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	302	\$19,116.21		
	1-575/600-80-700GT	✓	✓	✓		✓		100	80	75	56	38	29	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	312	\$20,491.60		
	1-575/600-112-700GT	✓	✓	✓		✓		140	112	100	75	51	38	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	312	\$23,146.73		
	1-575/600-160-700GT	✓	✓	✓		✓		200	160	150	112	77	57	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	308	\$25,408.24		
	1-575/600-200-700GT	✓	✓	✓		✓		250	200	220	164	113	84	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	308	\$27,018.18		
	1-575/600-240-700GT	✓	✓	✓		✓		300	240	250	186	128	95	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	323	\$28,408.71		
	1-575/600-320-700GT	✓	✓	✓		✓		400	320	350	261	179	134	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	352	\$31,255.04		
	1-575/600-480-700GT	✓	✓	✓		✓		600	480	500	373	256	191	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	402	\$43,955.31		
BE	Baumer Rotary Encoder for Above Panels																															\$597.50		
	HS35P-00360-H-ABZCM110BE-100-5																																	
	HS35P-00360-PH-ABZC-D31SR10-B-E-100-IP65																																	
	For all Panels																																	
	1) Power Factor Correction capacitors not Included																																	
	2) Maximum Induction Generator Nameplate rating (HP) is based on SEW Eurodrive DRE High Efficiency motors 0-250hp, and GE Quantum LMV motors 350 and 500hp.																																	
	3) Actual motor voltage should be confirmed at time of order																																	

